

# EMERGENCY EXIT LIGHTS LEDER


SMT LED with lifespan 50,000 burning hours  
SMT LED surface mount emergency exit light



● **ES/M/W510RM (E)**

Running-man graphical exit signs  
comply to latest SS 563 & SS 508

● **ES/M/W5100**



Dimension: mm NTS

### TECHNICAL DATA

Mode of Operation	: Maintained
Lamp	: Maxspid 1W SMT LED Lamp
Rated Duration	: 2 hr and others
Mains Supply	: 230 Volts, 50/60Hz
Power Consumption	: > 2VA
Battery	: High temp nickel cadmium
Charge Monitor	: Green LED Ø5mm
Test Facility	: Micro switch
Safety Feature	: Low volt cut-off preventing battery overdischarge
Fitting Construction	: Electro galvanised steel with epoxy powder coating
Diffuser	: Fire retardant moulded acrylic
Mounting	: Wall or ceiling
Cable Entry	: Ø20mm K/O hole
Weight	: 2.5kg (gross)
Compliance	: SS 563 : Part 1 & 2, SS IEC 60598-2-22
Warranty	: 1 year

### KEY FEATURES

- > Using Surface Mount Technology LED
- > High Durability & Reliability
- > Low Heat
- > Low Maintenance
- > Low Power Consumption
- > No "Black Ends"

### ORDERING GUIDE (Please check with Sales Dept if customisation is required)

Single Sided	Double Sided	Legend
ES/M/W5100	ED/M/W5100	EXIT
ES/M/W5100 (R)	ED/M/W5100 (R/L)	EXIT ▶
ES/M/W5100 (L)	ED/M/W5100 (R/L)	◀EXIT
ES/M/W510RM	ED/M/W510RM	
ES/M/W510RM (E)	ED/M/W510RM (E/W)	
ES/M/W510RM (W)	ED/M/W510RM (E/W)	◀
ES/M/W510RM (S)		
ES/M/W510RM (N)		

Type and batch tested with  
PSB PLUS-LISTED LABEL

Surface Mount  
Internal Lfr  
Led Slim Exit Sign

IP30  
CLASS I